




Effect+ DL

Effect+ DL

**HIGH EFFICIENCY
DOWNLIGHT
UP TO 144LM/W**

**Choice of 4 lumen outputs
Low glare UGR<19
Wide range of accessories**

Drawing



Dimensions

25W: Outer Diameter Ø 140mm
25W: Cut out Ø 121,5mm

LED specifications

LED chip Bridgelux F90
Power Up to 42W
Lum. flux Up to 5880 lm
Efficiency Up to 144 lm/W
Color rendering RA90
CCT 2700K-4000K
Avg. lifetime (hours) 50.000h

Available Output	18W (2520lm) / 25W (3500lm) / 32W (4480lm) / 42W (5880 lm)
Available CCT	2700K / 3000K / 4000K
Beam angle	15° / 24° / 36° / 60°
Dimming option	Dali / Casambi
Accesorie options	Honeycomb filter (3mm) / Oval lens / Antiglare covers: Oval or Asymmetrical

Input	Up to 1050 mA	Tilting angle	30°	Material	Aluminium
Driver type	External	Rotation angle	355°	Color	black/white
Driver incl.	-	Warranty (Mod./driv.)	5 years	Protection	IP20

Installation	Recessed
Weight	700g

CONTACT HOFFT FOR SPECIFIC REQUESTS