




Effect+ TR

## EFFECT+ TR

HIGH EFFICIENCY  
TRACK SPOT  
UP TO 144LM/W

Choice of 4 lumen outputs  
Choice of 4 beam angles  
Wide range of accessories for  
glare control

### Drawing



### Dimensions

18W: ø90 x 90 x 160 mm  
25W: ø90 x 90 x 160 mm  
32W: ø100 x 95 x 170 mm  
42W: ø110 x 100 x 180 mm

### LED specifications

**LED chip** Bridgelux F90  
**Power** Up to 42W  
**Lum. flux** Up to 5880 lm  
**Efficiency** Up to 144 lm/W  
**Color rendering** RA90  
**CCT** 2700K-4000K  
**Avg. lifetime (hours)** 50.000h

|                           |   |
|---------------------------|---|
| <b>Available Output</b>   | 2520 / 3500 / 4480 / 5880 lm  |
| <b>Available CCT</b>      | 2700K / 3000K / 4000K   |
| <b>Beam angle</b>         | 15° / 24° / 36° / 60°   |
| <b>Dimming option</b>     | Dali / Casambi  |
| <b>Accessorie options</b> | Honeycomb filter (3mm) / Oval lens / Anti glare covers: Oval or Asymetrical |

|                     |                     |                              |         |                   |             |
|---------------------|---------------------|------------------------------|---------|-------------------|-------------|
| <b>Input</b>        | AC220-240V          | <b>Tilting angle</b>         | 0-90°   | <b>Material</b>   | Aluminium   |
| <b>Driver type</b>  | 600 / 800 / 1050 mA | <b>Rotation angle</b>        | 0-350°  | <b>Color</b>      | black/white |
| <b>Driver incl.</b> | Yes (adapter)       | <b>Warranty (Mod./driv.)</b> | 5 years | <b>Protection</b> | IP20        |

|                     |                                  |
|---------------------|----------------------------------|
| <b>Installation</b> | 3-phase track                    |
| <b>Weight</b>       | 0,6kg / 0,6 kg / 0,7 kg / 0,8 kg |

CONTACT HOFFT FOR SPECIFIC REQUESTS